**CLAIMS** 

1

1		as recited in claim 1, wherein said client computer system is a mini computer.
2	6.	A communication system for communicating between an information provider and a user
3		as recited in claim 1, wherein said client computer system is a mainframe computer.
4	7.	A communication system for communicating between an information provider and a user
5		as recited in claim 1, wherein said client computer system is a special purpose digital
6		computer.
7	8.	A communication system for communicating between an information provider and a user,
8 9 10		as recited in claim 1, wherein said client computer system has a Windows operating
₩ ₩ 9		system.
√	9.	A communication system for communicating between an information provider and a user,
Ф11 s		as recited in claim 1, wherein said client computer system has a Windows 95 operating
口12 山 口13 叮 口14		system.
™13 □	10.	A communication system for communicating between an information provider and a user,
드 14		as recited in claim 1, wherein said flient computer system has a Windows NT operating
15		system.
16	11.	A communication system for communicating between an information provider and a user,
17		as recited in claim 1, wherein said client computer system has a Macintosh operating
18		system.
19	12.	A communication system for communicating between an information provider and a user,
20		as recited in claim 1, wherein said client computer system has a Unix operating system.
21	13.	A communication system for communicating between an information provider and a user,
22		as recited in claim 1, wherein said client computer system has a Linux operating system.

1	14.	A communication system for communicating between an information provider and a user,
2		as recited in claim 1, wherein said client computer system has an OS/2 operating system.
3	15.	A communications system for communicating between an information provider and a
4		user, as recited in claim 1, wherein said local area network is a IPX network.
5	16.	A communications system for communicating between an information provider and a
6		user, as recited in claim 1, wherein said local area network is a IP network.
7	17.	A communications system for communicating between an information provider and a
□ □ 8		user, as recited in claim 1, wherein said information provider is an internet service
0 0 0 1 7 0		provider.
	18.	A communications system for communicating between an information provider and a
) 		user, as recited in claim 1, wherein said information provider is a software distributor.
直2 山	19.	A communications system for communicating between an information provider and a
143 11		user, as recited in claim 1, further comprising: a modem electrically connected to said
∏13 ☐14 ☐14	/	server computer to transmit data electronically to a telephone land line.
15	<b>2</b> 0.	A process for asymmetrically communicating between an information service provider
16		and a user, comprising:
17		(A) receiving data from said information service provider by a satellite
18		communications channel; and
19		(B) conveying said received data across a local area network to one or more digital
20		computer systems.
21	21.	A process for asymmetrically communicating between an information service provider
<b>, 22</b>		and a user, as recited in claim 20, further comprising:

1		(C) generating a request from said one or more digital computer systems to said
2		information service provider.
3	22.	A process for asymmetrically communicating between an information service provider
4		and a user, as recited in claim 20, further comprising:
5		(D) conveying said generated request to said information service provide by a land
6		line communication channel.
7	23.	A process for asymmetrically communicating between an information service provider
□ □ 8		and a user, as recited in claim 20, further comprising:
☐ 8 ☐ 9 √ ↓ 0		(D) conveying said generated request to said information service provide by a satellite
-10		communication channel
<u>ц</u> Й1	24.	A process for asymmetrically communicating between an information service provider
12		and a user, as recited in claim 20, further comprising:
12 13 14		(D) conveying said generated request to said information service provide by a wireless
14		communication charine.
15	25.	A process for asymmetrically communicating between an information service provider
16		and a user, as recited in claim 20, further comprising:
17		(D) conveying said generated request to said information service provide by a routed
18		communication channel.
19	26.	A process for asymmetrically communicating between an information service provider an
20		a user, as recited in claim 20, further comprising: receiving data from said satellite
21		communications channel into computer hardware memory.
22	27.	A process for asymmetrically communicating between an information service provider an
		1

1		a user, as recrited in claim 20, further comprising: checking to determine it said received
2		data has an IP format.
3	28.	A process for asymmetrically communicating between an information service provider
4		and a user, as recited in claim 20, further comprising: checking to determine if said
5		received data has a packetized format.
6	29.	A process for asymmetrically communicating between an information service provider
7		and a user, as recited in claim 20, wherein said one or more digital computer systems are
<b>□</b> 8		connected electrically by a local area network.
	<b>30</b> .	A method for controlling the transfer of information between an information service
10		provider and a user, comprising:
		(A) receiving data from said information service, wherein said received data has a
<u>1</u> 12		protocol identifier;
112 113 114 114		(B) determining the protocol of said received data; and
- 14 ⊨		(C) delivering said data according to said protocol of said received data to a client
15		computer.
16	31.	A method for controlling the transfer of information between an information service
17		provider and a user, as recited in claim 30, further comprising:
18		(D) receiving a return packet of data from said client computer.
19	32.	A method for controlling the transfer of information between an information service
20		provider and a user, as recited in claim 31, further comprising:
21		(E) delivering said returned packet of data from said client computer to said
22		information service provider.

1	<i>j</i> 33.	A computer program to manage communications between an information service
2		provider and a user, comprising:
3		(A) a routine for receiving information from said information service;
4		(B) a routine for testing said received/information to determine the source of said
5		information;
6		(C) a routine for delivering said redeived information to a digital computer system.
7	34.	A computer program to manage communications between an information service
日 第 第 第 第 9 7 0		provider and a user, as recited in claim 33, further comprising: a routine for determining
₩ ₩ 9		an age value for said received information.
₹ <b>1</b> 0	35.	A computer program to manage communications between an information service
М1		provider and a user, as recited in claim 33, further comprising: a routine for replacing old
<b>1</b> 2		received information with newer received information.
□2 □3 □4	36.	A system for managing the communications between an information service provider and
<u> </u>		a user, comprising:
15		(A) a digital computer system connected to a local area network;
16	-,,,,,,,	(B) a first interface device for communicating between said local area network and a
17		satellite communication channel;
18		(C) a first connection between said satellite communication channel and a source of
19		information;
20		(D) a second connection between said land line communication channel and a source
21		of information; and
22		(E) a means for controlling the flow of information between said digital computer

1		system and said source of information.
2	37.	A system for managing the communications between an information service provider and
3		a user, as recited in claim 36 further comprising a second interface device for
4		communicating between said local area network and a land line.
5	38.	A system for managing the communications between an information service provider and
6		a user, as recited in claim 36 further comprising a second interface device for
7		communicating between said local area network and a wireless channel.
트8 교	39.	A system for managing the communications between an information service provider and
□8 □9 □10 □11		a user, as recited in claim 36 further comprising a second interface device for
<u></u>		communicating with said local area network to a satellite.
	40.	A system for managing the communications between an information service provider and
12 12 113 113		a user, as recited in claim 36 further comprising a second interface device for
<b>1</b> 13		communicating with said local area network to a routed channel.
	/	
	C)	